



CYCLONE CHILLER SPECIFICATIONS

MODEL NO.	HP/TONS	NOMINAL BTUH	VOLTS / PHASE	AMPS.	WATTS	L	W	H	CL	CH	RL	R134A REFRIGERANT CHARGE (OZ)	AIR OUTPUT (CFM)	MINIMUM WATER FLOW RATE COIL (GPM)	WEIGHT (LBS.)	SHIPPING WEIGHT (LBS.)	SHIPPING DIMENSIONS (INCHES)
CY-2	1/5	1,810	115	3.4	391	14"	12"	11"	7"	3"	7 1/2"	5.5	220	6	40	44	27x16x16
CY-3	1/4	3,080	115	5.4	621	14"	12"	11"	9"	3"	7 1/2"	5.75	240	8	42	47	27x16x16
CY-4	1/3	4,050	115	7.2	828	18 1/2"	13"	11"	10"	3"	7 1/2"	7.5	260	10	51	56	28x18x16
CY-5	1/2	6,000	115	9.5	1092	18 1/2"	15 1/2"	13"	11"	4"	9"	9.5	350	12	91	100	33x26x25
CY-6	1/2	6,000	230/1	4.8	1104	18 1/2"	15 1/2"	13"	11"	4"	9"	9.5	350	12	91	100	33x26x25

IMPORTANT: NEVER BEND THE HOSE LESS THAN A 6 INCH RADIUS. DO NOT SUBMERGE HOSE IN WATER BEYOND THE TITANIUM RISER.

ALL DIMENSIONS ARE APPROXIMATE AND CAN CHANGE WITHOUT NOTICE



Aqua Logic, Inc.  
8268 Clairemont Mesa Blvd. Suite 302  
San Diego, CA 92111

TITLE: CY-2,3,4,5 & 6  
CHILLER SPECIFICATIONS

LAST UPDATE: 7-20-06

DATE: 5-9-06

FILE: CY-2,3,4,5 & 6 SPEC

BY: CE