


### TRIMLINE CYCLONE CHILLER SPECIFICATIONS

MODEL NO.	HP/TONS	NOMINAL BTUH	VOLTS / PHASE	AMPS.	WATTS	L	W	H	CL	CH	RL	MINIMUM WATER FLOW RATE PAST COIL (GPM)	R134A REFRIGERANT CHARGE (OZ)	AIR OUTPUT (CFM)	WEIGHT (LBS.)	SHIPPING WEIGHT (LBS.)	SHIPPING DIMENSIONS (INCHES)
TLC-2	1/5	1,810	115	3.4	391	12"	9"	20 1/2"	7"	3"	7 1/2"	6	5.5	220	48	56	26x16x29
TLC-3	1/4	3,080	115	5.4	621	12"	9"	20 1/2"	9"	3"	7 1/2"	8	5.75	240	55	56	26x16x29
TLC-4	1/3	4,050	115	7.2	828	15 1/2"	9"	21 1/2"	10"	3"	7 1/2"	10	7.5	260	60	67	26x16x30
TLC-5	1/2	6,000	115	9.5	1092	15"	9"	23 1/2"	11"	4"	9"	12	9.5	350	80	90	26x16x32
TLC-6	1/2	6,000	230/1	4.8	1104	15"	9"	23 1/2"	11"	4"	9"	12	9.5	350	80	90	26x16x32

IMPORTANT: NEVER BEND THE HOSE LESS THAN A 6 INCH RADIUS. DO NOT SUBMERGE HOSE IN WATER BEYOND THE TITANIUM RISER.

ALL DIMENSIONS ARE APPROXIMATE AND CAN CHANGE WITHOUT NOTICE

 Aqua Logic, Inc.  
8268 Clairmont Mesa Blvd. Suite 302  
San Diego, CA 92111

TITLE: TLC-2 THRU TLC-6  
CHILLER SPECIFICATIONS

LAST UPDATE: 7-20-06

DATE: 4-28-06

FILE: TLC-2,3,4,5 & 6 SPEC

BY  
CE